

AD-A089 059

ARMY MOBILITY EQUIPMENT RESEARCH AND DEVELOPMENT COMM--ETC F/6 13/6
VERIFICATION TEST OF THE CHANGE-OF-PACE STATION WAGON.(U)

JUL 80 E J DOWGIALLO, I R SNELLINGS

DOE-IAA-EC-77-A-31-1042

NL


UNCLASSIFIED

NERADCOM-2304

For []
ALL []



END
DATE
FILMED
10-80
DTIC



AD A089059

LEVEL II

12 B.S.

AD

Report 2304

VERIFICATION TEST OF THE CHANGE-OF-PACE STATION WAGON

by
Edward J. Dowgiallo, Jr.
Ivan R. Snellings
and
William H. Blake

July 1980

SDTIC
ELECTE
SEP 15 1980
A

Approved for public release; distribution unlimited.

DDC FILE COPY



U.S. ARMY MOBILITY EQUIPMENT
RESEARCH AND DEVELOPMENT COMMAND
FORT BELVOIR, VIRGINIA

80 9 15 016

Destroy this report when it is no longer needed.
Do not return it to the originator.

(14) MFERADCOM-2304

(12) 236

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 2304	2. GOVT ACCESSION NO. AD-A089059	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) VERIFICATION TEST OF THE CHANGE-OF-PACE STATION WAGON	5. TYPE OF REPORT & PERIOD COVERED Test Report	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Edward J. Dowgiallo, Jr. Ivan R. Snellings and William H. Blake	8. CONTRACT OR GRANT NUMBER(s) Interagency Agreement DOE-IA-EC-77-A-31-1042	9. SECURITY CLASS. (of this report) Unclassified
10. PERFORMING ORGANIZATION NAME AND ADDRESS Electrochem Div; Elec Pwr Lab; US Army Mobility Equipment Research and Development Command; Fort Belvoir, VA 22060	11. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	12. REPORT DATE Jul 80
13. CONTROLLING OFFICE NAME AND ADDRESS US Army Mobility Equipment Research and Development Command; Fort Belvoir, VA 22060	14. NUMBER OF PAGES 25	15. SECURITY CLASS. (of this report) Unclassified
16. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Prepared for Dept of Energy; Assistant Secretary for Conservation and Solar Energy; Division of Electric and Hybrid Vehicles	17. DECLASSIFICATION/DOWNGRADING SCHEDULE	
18. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
19. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
20. SUPPLEMENTARY NOTES		
21. KEY WORDS (Continue on reverse side if necessary and identify by block number) Electric Vehicle Lead Acid Battery Battery		
22. ABSTRACT (Continue on reverse side if necessary and identify by block number) The Change-of-Pace, an electric four-passenger station wagon, was tested at MERADCOM to verify conformity to the Department of Energy Performance Standards for Demonstrations, published in the Federal Register, 30 May 1978, Part V. The Change-of-Pace is manufactured in Cleveland, Ohio, by Electric Vehicles Associates. It is a converted AMC Pacer station wagon. It is powered by 20 6-volt batteries that are connected to the motor through an SCR controller actuated by a foot pedal to control motor speed. The 22-horsepower motor drives the rear wheels through an automatic transmission. Regenerative braking is provided.		

DD FORM 1, JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED


SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

403260

20

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

CONTENTS

Section	Title	Page
	ILLUSTRATIONS	iv
I	SUMMARY	1
II	INTRODUCTION	1
III	OBJECTIVES	1
IV	DESCRIPTION OF TEST VEHICLE	2
V	TEST RESULTS	8
	APPENDIX - VEHICLE SUMMARY DATA SHEET	10

Accession For	
NTIS Grant	<input checked="" type="checkbox"/>
DDC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability/	
Dist	Availability/
<i>A</i>	Special

ILLUSTRATIONS

Figure	Title	Page
1	EVA Change-of-Pace Station Wagon	3
2	Dashboard of the Change-of-Pace Station Wagon	4
3	Rear Battery Compartment	5
4	Front Battery Compartment with SCR Controller and Auxiliary Battery Charger	6
5	Front Battery Compartment with SCR Controller and Traction Battery Charger	7

VERIFICATION TEST OF THE CHANGE-OF-PACE STATION WAGON

I. SUMMARY

The Change-of-Pace, manufactured by Electrical Vehicle Associates (EVA), was tested during the period from 14 July 1978 to 11 September 1978. Complete test results are contained in Section V. Part of the verification test results are summarized below:

Acceleration: 50 km/h (31.1 mi/h) in 13 s.

Range: 51 km (31.7 m) driving 86 cycles of SAE J227a/type C driving cycle.

Forward Speed: 80 km/h (49.7 mi/h) for 39 min on MERADCOM Track with 5-percent grade.

Gradeability at Speed: At 25 km/h (15.5 mi/h) can traverse 13.8-percent grade (calculated)

Gradeability Limit: 27.9-percent grade for 20 s (calculated).

II. INTRODUCTION

The EVA Change-of-Pace electric vehicle was operated to verify conformity to the Department of Energy "Performance Standards for Demonstrations," published in the Federal Register, 30 May, 1978, Part V. The results of that testing, as performed by the U.S. Army Mobility Equipment Research and Development Command (MERADCOM), as well as other descriptive data concerning the vehicle, are presented in this report.

III. OBJECTIVES

The objectives of this test were to examine the EVA Change-of-Pace for suitability of those aspects of vehicle and component operating characteristics as outlined by the Department of Energy's "Performance Standards for Demonstration."

IV. DESCRIPTION OF TEST VEHICLE

The EVA Change-of-Pace Electric Station Wagon is an electrified version of an AMC Pacer wagon, converted by Electric Vehicle Associates, Inc., 9100 Bank St., Cleveland, OH 44125. The vehicle has a curb weight of 1941.4 kg (4280 lb) and loaded with cargo and driver has a gross vehicular weight of 2177.3 kg (4800 lb) (Figure 1).

The EVA Change-of-Pace Station Wagon (Pacer) comes equipped with standard lighting, windshield wipers and washers, speedometer, and odometer. The heater and defroster obtain hot air produced by an Espar gasoline-fired hot-air heater, rated at about 2000 Kcal/h (8000 Btu/h), and fueled from a 2½-gal fuel tank. Instrumentation peculiar to electric vehicles includes a 0- to 120-volt three-color band voltmeter, an amperemeter, 0-350A, and an auxiliary battery voltmeter (Figure 2).

The Pacer comes equipped with a Chrysler 904 3-speed automatic transmission with a lockup torque converter. It has front coil spring and rear leaf-spring suspension, with an anti-sway bar, heavy-duty shocks and an added rear leaf modifying the rear suspension. The gear ratios are 2.45:1, 1.45:1, and 1.00:1.

Braking in the Pacer is provided by hydraulic front-disc and hydraulic rear-drum brakes, with a mechanically actuated rear-drum parking brake. Regenerative braking is available as an option. The vehicle comes equipped with Michelin 6.70 R14 XAC tires, inflated front and rear to 3.36×10^5 torr (65 lbf/in.²).

The heart of the Pacer is, of course, the propulsion system, and the batteries for the Pacer are 20 145-ampere-hour rated Trojan J244 lead acid, deep-discharge batteries.

These batteries are fused by a Fusetron, FRN250 ampere fuse. The auxiliary battery is a 25-A-h, 12-V unit (Figures 3, 4, and 5). The motor in this propulsion system is an EVA Series wound motor, rated at 120 V, 200 A continuous, 16.4 kW (22 hp). The maximum rated r/min is 4599. Finally, to control the motor the Pacer uses a Cableform Pulsomatic MK10 SCR-type controller. This unit is rated at 140-V d.c., 135-A continuous, 300-A for 3 min maximum service (Appendix).



Figure 1. EVA change-of-pace station wagon.



Figure 2. Dashboard of the change-of-pace station wagon.



Figure 3. Rear battery compartment.




Figure 4. Front battery compartment with SCR controller and auxiliary battery charger.




Figure 5. Front battery compartment with SCR controller and traction battery charger.

V. TEST RESULTS

The following are the results of the Verification Test performed at MERADCOM during the period of 14 July 1978 to 11 September 1978. Paragraphs are referenced to the DOE "Performance Standards for Demonstrations" criteria.

- (a) Acceleration. 50 km/h in 13 s.
- (b) Gradeability at speed. At 25 km/h can traverse a 13.8-percent grade based on calculation from acceleration tests at 80-percent depth of battery discharge (DOD).
- (c) Gradeability limit. Vehicle should start and climb forward on a 27.9-percent grade for at least 20 s based on drawbar pull tests at 80-percent DOD.
- (d) Forward speed capability. Maintained 80 km/h for 39 minutes on MERADCOM test track with a 5-percent grade.
- (e) Range. SAE J227a C cycle on level ($\pm 1\%$) terrain, 51 km, and 86 cycles. The auxiliary battery was discharged before completion of this test due to an inoperative traction battery-powered charge circuit. The battery was replaced with a fully charged one and the test was completed. The manufacturer now claims to have an operating charge circuit.
- (f) Battery recharge time. After an 80-percent discharge, recharged with charger model Battery Marshall Mark 3 (220 VAC, 50 A) on board the vehicle for 10 h; after recharge, vehicle operated for 50 km to SAE J227a C cycle regime.
- (g) Recharge control. Timer, with a maximum setting of 16 h.
- (h) Energy consumption. Only nonelectrical energy use is optional gasoline-fueled heater.
- (i) Battery life. Warranty period of 12 mth. Battery type — TROJAN MODEL T-135 lead acid, 75-A for 135 min. Battery consisted of 60 cells connected in series in 20 modules, nominal voltage was 120 V.
- (j) State-of-charge meter. Voltmeter, three color bands.
- (k) Odometer. Yes.
- (l) Passenger comfort heater. Optional.

(m) Documentation. Satisfactory. The following were provided: User manuals, maintenance (service) manuals, and parts lists.

(n) Emissions. Did not evaluate.

(o) Safety. The Department of Transportation is performing these evaluations; however, MERADCOM performed the following limited checks:

(1) Electrical isolation. The electrical propulsion circuit is isolated by design; however, voltages above 50 V capable of sustaining currents greater than 60 mA were measured from a battery terminal to the frame. Electrical shocks to personnel occurred while they were measuring specific gravities even when only touching the battery cases. Battery manufacturers claim that leakage currents and voltages are conducted through acid vapors which have condensed on the battery cases during charge and discharge.

(2) Safety standards 208 and 301. The Department of Transportation will check compliance. Comments: Rear battery holddown brackets were too close to battery terminals.

(3) Battery caps were standard golf cart type. Flame-barrier characteristics were not tested.

(4) Ventilation of battery compartment. All battery compartments should be open during charge and adequate ventilation provided to carry off acid vapor and to avoid hydrogen-oxygen explosions. This should be scrupulously followed before closing the vehicle for a time after charging to allow residual hydrogen gas to dissipate.

(5) Battery emergency disconnection. No mechanically linked disconnect was provided. However, the vehicle has a master, normally open, contactor rated at 2000 A designed to break short circuits, which is key-switch operated and powered from the 12-V auxiliary battery. There are also two relays, rated at 1500 A each, that apply the battery voltage through the SCR controller to the motor. These contacts are normally open and are closed with power from the 120-V traction battery. The vehicle also has a torque converter and automatic transmission with a neutral shift position. The battery packs are each fused at 250 A.

(6) Parked temperature effect. Vehicle was parked for two 8-h periods at temperatures of -25° C and 50° C. Subsequent operation revealed no apparent damage to the vehicle or hazard to personnel.

APPENDIX

VEHICLE SUMMARY DATA SHEET

1. Vehicle Manufacturer Name and Address:

Electric Vehicle Associates Inc.
9100 Bank Street
Cleveland, Ohio 44125
216-524-8418

2. Vehicle Description

Name: Change-of-Pace
Model: Station Wagon
Availability: Out of production
Price: —

3. Vehicle Weight

Curb Weight: 1991 kg (4380 lb)
Payload Weight: 272.7 kg (600 lb)
Gross Weight: 2264 kg (4980 lb)

4. Vehicle Size

Wheelbase: 2.553 m (100.5 in.)
Length: 4.483 m (176.5 in.)
Width: 1.943 m (76.5 in.)
Headroom: 0.977 m (38.45 in.)
Legroom: 1.033 m (40.68 in.)

5. Auxiliaries and Options

No. Lights: 11

a. Head; Parking; Signal; Dome; Tail; Tag;

b. Backup; Stop; Emergency; Dash; Running Light

Windshield Wipers: Yes

Windshield Washers: Yes

Defroster: Yes

Heater: Yes

Radio: No

Fuel Gage: No

Ampmeter: Yes

Tachometer: No

Speedometer: Yes

Odometer: Yes

No. Mirrors: 2

Power Steering: No

Power Brakes: No

Transmission Type: Automatic

6. Propulsion Batteries

Type T-135

Manufacturer: Trojan

No. of Modules: 20

S/N: N/A

No. Cells: 60

Battery Voltage: 120V

AH Capacity: 168 A-H

Battery Size: H0.267 m (10½ in.) W01.84 m (7¼ in.) L0.267 m (10½ in.)

Battery Weight: 34.6 kg (76 lb)

Battery Age: New

Battery Rate: 75 A

Battery Cycles: 5 Cycles

7. Auxiliary Battery

Type: Lead/Acid

Manufacturer: Gould

No. Cells: 6

Battery Voltage: 12V

AH Capacity: 25 A-H

Battery Rate: 20 H

8. Controller

Type: SCR
Manufacturer: Cableform
Voltage Rating: 140
Current Rating: 135A, 300A max-3 min.
Size: H0.254 m (10 in.) W0.127 (5 in.) L0.610 (24 in.)
Weight: 22.7 kg (50 lb)

9. Propulsion Motor

Type: Series
Manufacturer: EVA
Insulation Class: H
Voltage Rating: 120
Current Rating: 200 A Cont.
HP Rating: 16.4 kW (22 hp)
Max. 5 Min. Rating: N/A
Size: 0.356 m (14 in.) 0.305 m (12 in.)
Weight: 109 kg (240 lb)
Rated Speed: N/A
Max. Speed: 4599 RPM

10. Body

Type: S/W
Manufacturer: AMC
No. Doors: 2
Type: Hinged
No. Windows: 3
Type: 2 crank; 1 swing
No. Seats: 3
Type: 2 bucket; 1 bench
Cargo Volume: 1.5 m³ (52.45 ft³)
Cargo Dimensions: 1.7x1.16x0.79 (m) (5.5x3.8x2.6) (ft)

11. Chassis

Type Frame: Unitized
Manufacturer: AMC
Type Material: Steel
Modifications: None
Type Springs: Coil (Front) Leaf (Rear with Added Leaf)
Type Shocks: Hydraulic
Axle Type Front: Independent
Axle Type Rear: Solid
Axle Manufacturer: AMC
Drive Line Ratio: 3.58:1
Type Brakes Front: Disc
Type Brakes Rear: Drum
Regenerative Brakes: Yes
Tire Type: Tube 8 PR.
Manufacturer: Michelin Radial
Size: 6.70 R14 x AC
Pressure: 448.2 kPa (65 PSI) Front and Rear

12. Battery Charger

Type: SCR
Manufacturer: EVA
On or Off Board: On
Input Voltage: 220
Peak Current: 50 A
Recharger Timer: Yes
Weight: 9.1 kg (20 lb)
Automatic Turn Off: Yes (Timer w/Voltage Sense)

DISTRIBUTION FOR MERADCOM REPORT 2304

No. Copies	Addressee	No. Copies	Addressee
	Department of Defense	1	Commander US Army Troop Support & Aviation Materiel Readiness Com ATTN: DRSTS-MES (1) 4300 Goodfellow Blvd St Louis, MO 63120
1	Director, Technical Information Defense Advanced Research Projects Agency 1400 Wilson Blvd Arlington, VA 22209		
1	Director Defense Nuclear Agency ATTN: TITL Washington, DC 20305	1	Director Petrol & Fld Svc Dept US Army Quartermaster School Fort Lee, VA 23801
1	Defense Technical Information Ctr Cameron Station Alexandria, VA 22314	1	Commander US Army Electronics Research & Development Command Technical Library Division ATTN: DELSD-L Fort Monmouth, NJ 07703
	Department of the Army		
1	Commander, HQ TRADOC ATTN: ATEN-ME Fort Monroe, VA 23651	1	HQ, 193D Infantry Brigade (Pan) ATTN: AFZU-FE APO Miami 34004
1	Technical Library Technical Systems Laboratory Aberdeen Proving Ground, MD 21010	1	Special Forces Detachment, Europe ATTN: PBO APO New York 09050
1	Commander US Army Aberdeen Proving Ground ATTN: STEAP-MT-U (GE Branch) Aberdeen Proving Ground, MD 21005	1	Commander Rock Island Arsenal ATTN: SARRI-LPL Rock Island, IL 61201
1	Director US Army Materiel Systems Analysis Agency ATTN: DRXSY-CM Aberdeen Proving Ground, MD 21005	1	HQDA ODCSLOG DALO-TSE Room 1E588 Pentagon, Washington, DC 20310
1	Director US Army Materiel Systems Analysis Agency ATTN: DRXSY-MP Aberdeen Proving Ground, MD 21005	1	Commander Headquarters, 39th Engineer Battalion (Cbt) Fort Devens, MA 01433
		1	Commander and Director USA FESA ATTN: FESA-TS Fort Belvoir, VA 22060

No. Copies	Addressee	No. Copies	Addressee
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL (Tech Lib) White Sands Missile Range, NM 88002	3	Security Ofc (for liaison officers), DRDME-S
1	HQ, USAEUR & Seventh Army Deputy Chief of Staff, Engineer ATTN: AEAEN-MT-P APO New York 09403	2	Tech Library, DRDME-WC
1	HQ, USAEUR & Seventh Army Deputy Chief of Staff, Operations ATTN: AEAGC-FMD APO New York, 09403	1	Programs & Anal Dir, DRDME-U
2	District Engineer ATTN: SWFED-MF FWD Corps of Engineers P.O. 17300 Fort Worth, TX 76102	1	Pub Affairs, Ofc, DRDME-I
	MERADCOM	1	Ofc of Chief Counsel, DRDME-L
1	Commander, DRDME-Z Technical Director, DRDME-ZT Assoc Tech Dir/R&D, DRDME-ZN Assoc Tech Dir/Engrg & Acq, DRDME-ZE Spec Asst/Matl Asmt, DRDME-ZG Spec Asst/Scs & Tech, DRDME-ZK CIRCULATE		Department of the Navy
1	Chief, Ctrmine Lab, DRDME-N Chief, Engy & Wtr Res Lab, DRDME-G Chief, Elec Pwr Lab, DRDME-E Chief, Camo & Topo Lab, DRDME-R Chief, Mar & Br Lab, DRDME-M Chief, Mech & Constr Eqpt Lab, DRDME-H Chief, Ctr Intrus Lab, DRDME-X Chief, Matl Tech Lab, DRDME-V Director, Product A&T Directorate, DRDME-T CIRCULATE	2	Commander, Naval Facilities Engineering Command Department of the Navy ATTN: Code 032-B 062 200 Stovall St Alexandria, VA 22332
100	Electrochemical Div, DRDME-EC	1	US Naval Oceanographic Office Navy Library/NSTL Station Bay St Louis, MS 39522
3	Tech Reports Ofc, DRDME-WP	1	Library (Code L08A) Civil Engineering Laboratory Naval Construction Battalion Ctr Port Hueneme, CA 93043
		1	Naval Training Equipment Center ATTN: Technical Library Orlando, FL 32813
		3	Naval Weapons Center (Code 2605) China Lake, CA 93555
			Department of the Air Force
		1	HQ USAF/RDPT ATTN: Mr. Allan Eaffy Washington, DC 20330
		1	Mr. William J. Engle Chief, Utilities Branch HQ USAF/PREEU Washington, DC 20332
		1	US Air Force HQ Air Force Engineering & Svcs Ctr Technical Library FL 7050 Tyndall AFB, FL 32403

No. Copies	Addressee	No. Copies	Addressee
1	Department of Transportation Library, FOB 10A, M494-6 800 Independence Ave., SW Washington, DC 20591	1	Department of Transportation Library, FOB 10A. TAD-494.6 800 Independence Ave., SW Washington, DC 20591
1	Mr. Carl Anderson Energy Technology Demonstration SM-ALC/XAE McClellan AFB, CA 95652	1	A. D. Little ATTN: Brad Underhill 15 Acorn Park Cambridge, MA 02140
	Others	1	Advanced Ground Systems Eng ATTN: Dr. George Gelb 3270 E. 70th Street Long Beach, CA 90805
1	Professor Raymond R. Fox School of Engineering and Applied Science George Washington University Washington, DC 20052	1	Airesearch Manufacturing Co ATTN: Bob Rowlett Program Manager 2525 W. 190th Street Torrance, CA 90509
3	Electric Vehicle Associates, Inc. 9100 Banks Street Cleveland, OH 44125	1	Billings Energy Corporation ATTN: Mr. Hadden P.O. Box 555 Provo, UT 84601
	Department of Energy	1	Booz, Allen & Hamilton Inc. John F. Wing Transportation Consulting Div 4330 East West Highway Bethesda, MD 20014
200	ATTN: Walter J. Dippold 1000 Independence Ave. Mail Stop 5H044 Room 5H063 Forrestal Bldg Washington, DC 20585	1	Borisoff Engineering Co 7726 Burnet Ave Van Nuys, CA 91405
1	Albert Cook International Lead Zinc Research Organization, Inc. 292 Madison Ave New York, NY 10017	1	Cooper Development Association ATTN: Donald K. Miner, Manager 430 N. Woodward Ave Birmingham, MI 48011
1	Bernie Wachter DAO Corp 2101 L Street NW Washington, DC 20037	1	Cornell University Joe Rosson, Associate Director School of Engineering Phillips Hall Ithaca, NY 14853
1	C. Joseph Venuto 3043 Walton Road Plymouth Meeting, PA 19462	1	Department of Industry, Trade, & Commerce Fred Johnson, Special Vehicle Div Transportation Industries Branch Ottawa, Canada, K1A 085
1	J. Hampton Barnett Energy Demonstration and Tech 109 United Bank Building Chattanooga, TN 37401		

No. Copies	Addressee	No. Copies	Addressee
1	Department of Transportation Transportation Systems Center ATTN: Dr. Norman Rosenberg Cambridge, MA 02142	1	Lawrence Livermore Laboratory ATTN: Douglas Davis-MS-L-216 P.O. Box 808 Livermore, CA 94550
1	Electric Power Research Institute ATTN: Dr. Fritz R. Kalhammer	1	Los Alamos Scientific Labs Byron McCormick P.O. Box 1663 Los Alamos, NM 87545
1	Ralph Ferraro 3412 Hillview Avenue P.O. Box 10412 Palo Alto, CA 94304	1	NASA - Lewis Research Center ATTN: J. S. Fordyce MS: 309-1 21000 Brookpark Road Cleveland, OH 44135
1	Energy Research and Development Corp ATTN: R. Childs, President 9135 Fernwood Drive Olmsted Falls, OH 44138	2	NASA - Lewis Research Center ATTN: H. J. Schwartz MS: 500-215 21000 Brookpark Road Cleveland, OH 44135
1	ESB, Inc. 5 Penn Center Plaza Philadelphia, PA 19103	1	Petro-Electric Motors, Ltd ATTN: Victor Wouk, Consultant 342 Madison Avenue, Suite 831 New York, NY 10017
1	General Electric Corporate Research & Development ATTN: Gene Rowland Program Manager P.O. Box 8 Schenectady, NY 12301	1	Purdue University IIES A.A. Potter Engineering Center ATTN: Dr. R. E. Goodson W. Lafayette, IN 47907
1	General Research Corporation ATTN: John Brennand 5383 Hollister Avenue Santa Barbara, CA 93105	1	Society of Automotive Engineers, Inc. William Toth, Staff Engineer 400 Commonwealth Warrendale, PA 15096
1	General Services Administration Federal Supply Service ATTN: Mel Globeman Washington, DC 20406	1	United States Postal Service ATTN: Dick Bowman Office of Fleet Mgmt Delivery Services Dept Washington, DC 20260
1	General Services Administration Federal Supply Service ATTN: R. L. Ullrich Washington, DC 20406	1	United States Postal Service ATTN: Donn Crane, Director Office of Fleet Mgmt Delivery Services Dept Washington, DC 20260
2	Jet Propulsion Laboratory ATTN: T. Barber 4800 Oak Grove Drive Pasadena, CA 91103		

No. Copies	Addressee
1	United States Postal Service Research & Development Lab ATTN: Lewis J. Gerlach Program Manager 11711 Park Lawn Drive Rockville, MD 20852
1	United States Postal Service ATTN: Thomas W. Martin, Manager Vehicle Services Branch Western Region San Bruno, CA 94099
1	University of California Jack Bolger Lawrence Berkeley Labs Berkeley, CA 94720
1	Westinghouse R&D Center ATTN: G. Frank Pittman, Jr. 1310 Beulah Road Pittsburgh, PA 15235
1	Marjorie L. McClanahan Chemical Process Unit Materials Technology Aeronutronic Division Ford Aerospace & Communications Corporation Ford Road Newport Beach, CA 92663
1	Clinton Christianson Argonne National Laboratory 9700 South Lass Avenue Argonne, IL 60439
1	F. J. Liles 705 Buffalo Drive Arlington, TX 76013
1	C. Grandy Union Electric Co P.O. Box 149 St Louis, MO 63166